

#270 Grade Natural Reinforced Tape

Description: Fiberglass reinforced, strippable natural kraft carton sealing tape, manufactured with water activated adhesive.

Construction (per 3000 square feet):

Top Ply:	25.0 Lb. Natural Kraft Paper (virgin fibers)
Bottom Ply:	30.0 Lb. Natural Kraft Paper (virgin fibers)
Laminating Adhesive:	15.5 Lb. High Melt Index Polypropylene Based Co-Polymer
Remoistenable Adhesive:	16.0 Lb. Chemically Grafted Starch Based Co-Polymer Adhesive Designated as #911.
MD Reinforcement:	5.33 Lb. (2-2-1-1-2-2) 75 Fiberglass (per 3 inch), 1/2" spacing
CD Reinforcement:	3.01 Lb. (1-1-1) 150 Fiberglass, 17/32" spacing, 45 degree angle
Total Basis Weight:	94.8 Lb.

Physical Properties:

Caliper (mils):	7.5
MD Tensile (Lbs./in.):	86
CD Tensile (Lbs./in.):	32

Product Application:

Recommended using on average to heavyweight cartons up to 75 pounds.

Standard Sizes Available:

3 inch by 375 feet (8 rolls per carton) 3 inch by 450 feet (10 rolls per carton)

#270 Grade SnowWhite Reinforced Tape

Description: Fiberglass reinforced, strippable snowwhite kraft carton sealing tape, manufactured with water activated adhesive.

Construction (per 3000 square feet):

Top Ply:	25.0 Lb. White Kraft Paper (virgin fibers)
Bottom Ply:	30.0 Lb. Natural Kraft Paper (virgin fibers)
Laminating Adhesive:	15.5 Lb. High Melt Index Polypropylene Based Co-Polymer
Remoistenable Adhesive:	16.0 Lb. Chemically Grafted Starch Based Co-Polymer Adhesive Designated as #911.
MD Reinforcement:	5.33 Lb. (2-2-1-1-2-2) 75 Fiberglass (per 3 inch), 1/2" spacing
CD Reinforcement:	3.01 Lb. (1-1-1) 150 Fiberglass, 17/32" spacing, 45 degree angle
Total Basis Weight:	94.8 Lb.

Physical Properties:

Caliper (mils):	7.5
MD Tensile (Lbs./in.):	80
CD Tensile (Lbs./in.):	31

Product Application:

Recommended for use on average to heavyweight cartons up to 65 pounds.

Standard Sizes Available:

3 inch by 375 feet (8 rolls per carton) 3 inch by 450 feet (10 rolls per carton)